

"CT" PULLEYS FOR "AT" METRIC PITCH POLYURETHANE BELTS

CT10 (10 mm pitch) DESIGNED FOR 16 mm WIDE BELT

ALUMINIUM	DESCRIPTION	EXEC.	No. of TEETH	De	Df	Dm	F	L	d	FLANGE No.
	31 CT10 15	1F	15	45.90	51	32	21	31	8	16
	31 CT10 16	1F	16	49.05	54	35	21	31	8	18
	31 CT10 18	1F	18	55.45	60	40	21	31	8	21
	31 CT10 19	1F	19	58.60	66.5	44	21	31	8	24
	31 CT10 20	1F	20	61.80	66.5	46	21	31	8	24
	31 CT10 22	1F	22	68.15	75	52	21	31	8	27
	31 CT10 24	1F	24	74.55	83	58	21	31	8	29
	31 CT10 25	1F	25	77.70	83	60	21	31	8	29
	31 CT10 26	1F	26	80.90	87	60	21	31	8	31
31 CT10 27	1F	27	84.10	91	60	21	31	8	32	
31 CT10 28	1F	28	87.25	93	60	21	31	8	33	
31 CT10 30	1F	30	93.65	97	60	21	31	8	35	
31 CT10 32	1F	32	100.00	106	65	21	31	10	38	
31 CT10 36	1F	36	112.75	119	70	21	31	10	43	
31 CT10 40	1F	40	125.45	131	80	21	31	10	47	
31 CT10 44	2	44	138.20	-	88	21	31	10	-	
31 CT10 48	2	48	150.95	-	95	21	31	16	-	
31 CT10 60	2	60	189.10	-	110	21	31	16	-	

CT10 (10 mm pitch) DESIGNED FOR 25 mm WIDE BELT

ALUMINIUM	DESCRIPTION	EXEC.	No. of TEETH	De	Df	Dm	F	L	d	FLANGE No.
	40 CT10 15	1F	15	45.90	51	32	30	40	8	16
	40 CT10 16	1F	16	49.05	54	35	30	40	8	18
	40 CT10 18	1F	18	55.45	60	40	30	40	8	21
	40 CT10 19	1F	19	58.60	66.5	44	30	40	8	24
	40 CT10 20	1F	20	61.80	66.5	46	30	40	8	24
	40 CT10 22	1F	22	68.15	75	52	30	40	8	27
	40 CT10 24	1F	24	74.55	83	58	30	40	8	29
	40 CT10 25	1F	25	77.70	83	60	30	40	8	29
	40 CT10 26	1F	26	80.90	87	60	30	40	8	31
40 CT10 27	1F	27	84.10	91	60	30	40	8	32	
40 CT10 28	1F	28	87.25	93	60	30	40	8	33	
40 CT10 30	1F	30	93.65	97	60	30	40	8	35	
40 CT10 32	1F	32	100.00	106	65	30	40	10	38	
40 CT10 36	1F	36	112.75	119	70	30	40	10	43	
40 CT10 40	1F	40	125.45	131	80	30	40	10	47	
40 CT10 44	2	44	138.20	-	88	30	40	10	-	
40 CT10 48	2	48	150.95	-	95	30	40	16	-	
40 CT10 60	2	60	189.10	-	110	30	40	16	-	

CT20 pitch pulleys and bars are manufactured on request.

"CT" PULLEYS FOR "AT" METRIC PITCH POLYURETHANE BELTS

CT10 (10 mm pitch) DESIGNED FOR 32 mm WIDE BELT

ALUMINIUM	DESCRIPTION	EXEC.	No. of TEETH	De	Df	Dm	F	L	d	FLANGE No.
	47 CT10 18	1F	18	55.45	60	40	37	47	10	21
	47 CT10 19	1F	19	58.60	66.5	44	37	47	10	24
	47 CT10 20	1F	20	61.80	66.5	46	37	47	12	24
	47 CT10 22	1F	22	68.15	75	52	37	47	12	27
	47 CT10 24	1F	24	74.55	83	58	37	47	12	29
	47 CT10 25	1F	25	77.70	83	60	37	47	12	29
	47 CT10 26	1F	26	80.90	87	60	37	47	12	31
	47 CT10 27	1F	27	84.10	91	60	37	47	12	32
	47 CT10 28	1F	28	87.25	93	60	37	47	12	33
47 CT10 30	1F	30	93.65	97	60	37	47	12	35	
47 CT10 32	1F	32	100.00	106	65	37	47	12	38	
47 CT10 36	1F	36	112.75	119	70	37	47	16	43	
47 CT10 40	1F	40	125.45	131	80	37	47	16	47	
47 CT10 44	2	44	138.20	-	88	37	47	16	-	
47 CT10 48	2	48	150.95	-	95	37	47	16	-	
47 CT10 60	2	60	189.10	-	110	37	47	16	-	

CT10 (10 mm pitch) DESIGNED FOR 50 mm WIDE BELT

ALUMINIUM	DESCRIPTION	EXEC.	No. of TEETH	De	Df	Dm	F	L	d	FLANGE No.
	66 CT10 18	1F	18	55.45	60	40	56	66	10	21
	66 CT10 19	1F	19	58.60	66.5	44	56	66	10	24
	66 CT10 20	1F	20	61.80	66.5	46	56	66	12	24
	66 CT10 22	1F	22	68.15	75	52	56	66	12	27
	66 CT10 24	1F	24	74.55	83	58	56	66	12	29
	66 CT10 25	1F	25	77.70	83	60	56	66	12	29
	66 CT10 26	1F	26	80.90	87	60	56	66	12	31
	66 CT10 27	1F	27	84.10	91	60	56	66	12	32
	66 CT10 28	1F	28	87.25	93	60	56	66	12	33
66 CT10 30	1F	30	93.65	97	60	56	66	12	35	
66 CT10 32	1F	32	100.00	106	65	56	66	12	38	
66 CT10 36	1F	36	112.75	119	70	56	66	16	43	
66 CT10 40	1F	40	125.45	131	80	56	66	16	47	
66 CT10 44	2	44	138.20	-	88	56	66	16	-	
66 CT10 48	2	48	150.95	-	95	56	66	16	-	
66 CT10 60	2	60	189.10	-	110	56	66	16	-	

CT20 pitch pulleys and bars are manufactured on request