

# " T " METRIC PITCH PULLEYS

## T 5 (5mm pitch) DESIGNED FOR 10mm WIDE BELTS

ALUMINIUM	DESCRIPTION	EXEC.	No. of TEETH	Dp	De	Df	Dm	F	L	d	FLANGE No.	
	21 T5 10	1F	10	16.05	15.05	19.5	8	15	21	-	-	3
	21 T5 12	1F	12	19.25	18.25	23.0	11	15	21	-	1	
	21 T5 14	1F	14	22.45	21.45	25.0	13	15	21	-	2	
	21 T5 15	1F	15	24.05	23.05	28.0	16	15	21	6	4	
	21 T5 16	1F	16	25.06	24.60	32.0	18	15	21	6	5	
	21 T5 18	1F	18	28.80	27.80	32.0	20	15	21	6	6	
	21 T5 19	1F	19	30.40	29.40	36.0	22	15	21	6	8	
	21 T5 20	1F	20	32.00	31.00	36.0	23	15	21	6	8	
	21 T5 22	1F	22	35.15	34.15	38.0	24	15	21	6	9	
	21 T5 24	1F	24	38.40	37.40	42.0	26	15	21	6	13	
	21 T5 25	1F	25	39.95	38.95	44.0	26	15	21	6	12	
21 T5 26	1F	26	41.60	40.60	44.0	26	15	21	6	12		
21 T5 27	1F	27	43.20	42.20	48.0	30	15	21	8	11		
21 T5 28	1F	28	44.75	43.75	48.0	32	15	21	8	11		
21 T5 30	1F	30	47.95	46.95	51.0	34	15	21	8	16		
21 T5 32	1F	32	51.10	50.10	54.0	38	15	21	8	18		
21 T5 36	1F	36	57.45	56.45	64.0	38	15	21	8	23		
21 T5 40	1F	40	63.85	62.85	66.5	40	15	21	8	24		
21 T5 42	1F	42	67.00	66.00	70.0	40	15	21	8	26		
21 T5 44	2	44	70.20	69.20	-	45	15	21	8	-		
21 T5 48	2	48	76.55	75.55	-	50	15	21	8	-		
21 T5 60	2	60	95.65	94.65	-	65	15	21	8	-		

## T 5 (5mm pitch) DESIGNED FOR 16mm WIDE BELTS

ALUMINIUM	DESCRIPTION	EXEC.	No. of TEETH	Dp	De	Df	Dm	F	L	d	FLANGE No.
	27 T5 10	1F	10	16.05	15.05	19.5	8	21	27	-	3
	27 T5 12	1F	12	19.25	18.25	23.0	11	21	27	-	1
	27 T5 14	1F	14	22.45	21.45	25.0	13	21	27	-	2
	27 T5 15	1F	15	24.05	23.05	28.0	16	21	27	6	4
	27 T5 16	1F	16	25.06	24.60	32.0	18	21	27	6	5
	27 T5 18	1F	18	28.80	27.80	32.0	20	21	27	6	6
	27 T5 19	1F	19	30.40	29.40	36.0	22	21	27	6	8
	27 T5 20	1F	20	32.00	31.00	36.0	23	21	27	6	8
	27 T5 22	1F	22	35.15	34.15	38.0	24	21	27	6	9
	27 T5 24	1F	24	38.40	37.40	42.0	26	21	27	6	13
	27 T5 25	1F	25	39.95	38.95	44.0	26	21	27	6	12
27 T5 26	1F	26	41.60	40.60	44.0	26	21	27	6	12	
27 T5 27	1F	27	43.20	42.20	48.0	30	21	27	8	11	
27 T5 28	1F	28	44.75	43.75	48.0	32	21	27	8	11	
27 T5 30	1F	30	47.95	46.95	51.0	34	21	27	8	16	
27 T5 32	1F	32	51.10	50.10	54.0	38	21	27	8	18	
27 T5 36	1F	36	57.45	56.45	64.0	38	21	27	8	23	
27 T5 40	1F	40	63.85	62.85	66.5	40	21	27	8	24	
27 T5 42	1F	42	67.00	66.00	70.0	40	21	27	8	26	
27 T5 44	2	44	70.20	69.20	-	45	21	27	8	-	
27 T5 48	2	48	76.55	75.55	-	50	21	27	8	-	
27 T5 60	2	60	95.65	94.65	-	65	21	27	8	-	

## T 5 (5mm pitch) DESIGNED FOR 25mm WIDE BELTS

ALUMINIUM	DESCRIPTION	EXEC.	No. of TEETH	Dp	De	Df	Dm	F	L	d	FLANGE No.
	36 T5 10	1F	10	16.05	15.05	19.5	8	30	36	-	3
	36 T5 12	1F	12	19.25	18.25	23.0	11	30	36	-	1
	36 T5 14	1F	14	22.45	21.45	25.0	13	30	36	-	2
	36 T5 15	1F	15	24.05	23.05	28.0	16	30	36	6	4
	36 T5 16	1F	16	25.06	24.60	32.0	18	30	36	6	5
	36 T5 18	1F	18	28.80	27.80	32.0	20	30	36	6	6
	36 T5 19	1F	19	30.40	29.40	36.0	22	30	36	6	8
	36 T5 20	1F	20	32.00	31.00	36.0	23	30	36	6	8
	36 T5 22	1F	22	35.15	34.15	38.0	24	30	36	6	9
	36 T5 24	1F	24	38.40	37.40	42.0	26	30	36	8	13
	36 T5 25	1F	25	39.95	38.95	44.0	26	30	36	8	12
36 T5 26	1F	26	41.60	40.60	44.0	26	30	36	8	12	
36 T5 27	1F	27	43.20	42.20	48.0	30	30	36	8	11	
36 T5 28	1F	28	44.75	43.75	48.0	32	30	36	8	11	
36 T5 30	1F	30	47.95	46.95	51.0	34	30	36	8	16	
36 T5 32	1F	32	51.10	50.10	54.0	38	30	36	8	18	
36 T5 36	1F	36	57.45	56.45	64.0	38	30	36	8	23	
36 T5 40	1F	40	63.85	62.85	66.5	40	30	36	8	24	
36 T5 42	1F	42	67.00	66.00	70.0	40	30	36	8	26	
36 T5 44	2	44	70.20	69.20	-	45	30	36	8	-	
36 T5 48	2	48	76.55	75.55	-	50	30	36	8	-	
36 T5 60	2	60	95.65	94.65	-	65	30	36	8	-	

T20 pitch pulleys and bars are manufactured on request.